

Hall B0

Due to its location, equipment and the fact that it is at ground level, Hall B0 is ideal for a variety of uses. With 3,500 m² of gross exhibition space and utility conduits hidden beneath the parquet flooring, exhibition stands can be connected individually to electrical, water, telecommunication and data lines. In addition to the technical infrastructure of the partially air-conditioned exhibition hall, Hall B0 also features some interesting architectural details: for example, it can easily be converted into a stunning restaurant for up to 1,460 guests. Hall B0 can easily be combined with the ground floor of the foyer.

Location:

Ground floor

- Direct vehicle access for deliveries
- Vehicles may not drive into the hall itself
- Forklifts may only be used by the exhibition center's freight forwarder
- The maximum load-bearing capacities of the passenger and freight elevators must be observed at all times.

Suitable for:

Exhibitions, catering

Size/capacity:

3,500 m² usable exhibition space

Special features:

- Length 65 m, width 54 m
- Gross exhibition space: approx. 3,500 m²
- Clearance height: 4 m
- Walls: wood paneling
- Floors: oak timber parquet
- Permissible floor load: 2.0 t/m² (20 kN/m²)
- Permissible point load, 30 cm x 30 cm: 6 t (60 kN/m²)
- Suspension points in hall: 100 kg (1 kN) vertical, permanent grid approx. 5.10 m x 2.75 m
- Loading gates, size: 12.50 m wide x 4.50 m high
- Loading gates, number: 1, via Gate 21

Utilities:

- Lighting: 400 Lux/m²
- Ventilation system: partially air-conditioned
- Utility ducts: diagonal to longitudinal direction of hall, spacing 5 m, cross section 35 cm x 38 cm
- Water connection: DN 25/3.5 bar
- Waste water connection: DN 100
- Compressed air connection: DN 50/10 bar
- Electricity: up to 40 kW per connection (63 A CEE)
- Telecom system connections: analog telephone/fax
- External telecom connections: ISDN, T-DSL 1000/2000
- Network: Ethernet/RJ-45 static IP
- Cable television connections: available