

Room 04

Room 04 can be partitioned down the middle to form two smaller, identically equipped rooms. When the entire room is used, it has 200 m² of space and can accommodate 206 people in theater seating, 96 people with classroom seating and 112 people with banquet seating. That makes it ideal for smaller presentations, workgroup sessions or – if equipped with bistro tables and used in conjunction with the foyer – for catering purposes.

Location:

Ground floor

- Deliveries on north side of building via delivery entrance in foyer
- Alternate delivery: via two elevators (2 m wide, 3 m long, max. 2,000 kg) next to Room 5

Suitable for:

Smaller presentations, workgroup sessions, etc. If equipped with bistro tables, it can also be used for catering purposes in conjunction with the foyer.

Size/capacity:

200 m², seats 206 people in rows, 96 people with classroom seating, 112 with banquet seating

Special features:

- Room height 4.50 m
- Can be partitioned into 2 separate soundproof rooms (see Rooms 4a & 4b)
- Color of room: light gray

Media equipment:

Room 04 has an audio control booth equipped with a digital control console – i.e. the Cantus Console from Stagetec. The console is freely configurable, equipped with 32 fader sections and has direct access to the ICM's Nexus audio network. The average channel capacity is approximately 40 input channels and approximately 6 stereo sums. Two slave consoles with 20 fader sections are also available. They are used when the room is partitioned or can be used together with the room's other equipment.

Permanently installed media equipment:

- CD, MD, MC, DAT, 6 x radio mics
- Interpreter's system, 4 interpreter's booths
- Direct connections to other rooms possible

Movie screens:

The 3 movie screens (one each in Room 4, 4a and 4b) are rolled up onto drums and can be lowered when needed. The main screen in the room is 8 m x 4.5 m in size, and the screens for the partitioned rooms are both 4.5 m x 4.5 m in size.

Overhead machinery:

3 machine hoists (MZ 1 - 3) with a maximum capacity of 500 kg each are located above the performance area. MZ 1 (RR 60 tubular piping, 3/5 mm) is 9.8 m long and can be moved 1 m to the side.

Lighting:

There are two lighting hoists on the ceiling of the room. Highest position: 4.5 m above room level. Distance from stage: 2.5 m. Downlights are used to evenly light the room and the performance area. Dimmable connections are available for additional lighting. A variety of additional lighting equipment is also available (Frensel-lens and profile spotlights).

Equipment can be mounted on two lighting hoists above the performance area. Electrical connections can be provided for portable spotlights. The lighting system uses DMX 512 signals. DMX 512 connections are available at all spotlight positions and in the control booths. All equipment is connected using safety-contact plugs or CEE plugs.